

Walk-behind double drum road roller RWYL33C (Mechanical steering)

The machine is mainly used to compress on the asphalt, sand soil and gravel. It is also used to planish the lawn and playground.

Product characteristics

Double motor drive, double drum vibrate, mechanical steering.

1. China top brand diesel engine.
2. American light-duty variable plunger pump drives the machine stepless walking.
3. Double American brand cycloid hydraulic motors drive the machine walking.
4. Forward/reverse running, left/right steering and vibrating all controlled by the integrated control lever.
5. Ex-large plastic water tank, free from corrosion;
6. Dead-man safety control.



Type	RWYL33C
Run	
Speed	0—3.5km/h (Forward and back)
Climbing capacity in theory	25%
Compaction	
Static load forward/back	58/60N/cm
Nominal amplitude	0.5mm
Vibration frequency	65Hz
Exciting force	17-20kN
Water tank volume	38L
Working	
Drive	Variable plunger pump ,constant displacement hydraulic motor
Vibration	Mechanical drive, electromagnetic clutch
Engine	
Model	186F
Type	Diesel engine, air cooled, 4stroke, vertical type, single cylinder
Power	8.0hp/3600rpm
Fuel tank volume	3.5L
Lubricant L	1.1L
Fuel consumption	280g/kWh
Dimension	
Width of steel wheel	680mm
Diameter of steel wheel	355mm
Tread	500mm
Total length(keep handrail level)	2320mm
Total width	732mm
Total height(keep handrail upright)	1710mm
Packing size	1460x830x1910mm
Weight	
Working weight	700kg



