

HERCULES

25KG · 50 KG

ABC Trolley (Stored Pressure)



MODEL	FT03-042B-00	FT03-047C-00
Capacity	25 KG	50 KG
Extinguishing Agent	Multipurpose Dry Chemical Powder	
Propellant	N2	
Operation Method	Stored Pressure	
Test Standard	EN 1866	
Discharge Time	≥ 30 SEC	≥ 35 SEC
Throw Distance	≥ 10M	≥ 10M
Height	1000MM	1080MM
Width	450MM	450MM
Depth	435MM	435MM
Total Weight	52.0KG	82.0KG
Operating Temperature	-30°C - +60°C	
Working Pressure	15 BAR	15 BAR
Test Pressure	30 BAR	30 BAR
Fire Rating	A IB	A IIB
Part No.	FEM-FA-D25	FEM-FA-D50



EN3



SETSCO SG
APPROVED

Information

Effective against **class A fires** involving ordinary combustible materials like wood, paper, cloth, furning, plastics, rubber, etc, usually of an organic nature, in which combustion normally takes places with the formation of glowing embers.

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquefiable solids.

Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. Unroll hose.

3. Pull safety pin and turn on valve.

4. Aim at fire and squeeze handle

Ensure that extinguisher is located close to the work area and operators are trained in the use of extinguishers.