



# JAC FORKLIFT

Material Handling Experts From Automotive Quality

搬运专家源于汽车品质

2-3.5T Diesel Forklift-J Series  
CPCD20J CPCD25J CPCD30J CPCD35J



安徽江淮银联重型工程机械有限公司  
Anhui Jianghuai-Yinlian Heavy-Duty Construction Machine Co.,Ltd

# JAC FORKLIFT SPECIFICATION

## 2-3.5T Diesel Forklift-J Series



CPCD20J CPCD25J CPCD30J CPCD35J

Model	型号	Unit	CPCD20J	CPCD25J	CPCD30J	CPCD35J	
Load Capacity	额定起升重量	Kg	2000	2500	3000	3500	
Load Center	载荷中心距	mm	500	500	500	500	
Mast Lifting height	门架起升高度	mm	3000	3000	3000	3000	
Mast Free Lift	门架自由起升高度	mm	190	190	130	130	
Mast lifting Speed (With Load)	门架最大起升速度 (满载)	mm/s	530	530	435	368	
Mast tilt (Front/Rear)	门架倾角前/后		6° / 12°	6° / 12°	6° / 12°	6° / 12°	
Driving Speed	行驶速度	km/h	17	17	17	19	
Turning Radius	最小转弯半径	mm	2245	2300	2500	2575	
Ground clearance	最小离地间隙	mm	110	110	130	130	
Form Size	Length to face of forks	外形尺寸	全长(无货叉)	2536	2596	2740	2805
	Overall width	全宽	mm	1190	1190	1230	1230
	Height of overhead guard (cabin)	全高(至护顶架)	mm	2105	2105	2105	2105
	Height of mast, extended	全高(门架全伸出)	mm	4015	4015	4260	4270
Wheelbase	轴距	mm	1600	1600	1700	1700	
Tread	Fron	前轮距	mm	970	970	1000	1000
	Rear	后轮距	mm	970	970	970	970
Overhang (front)	前悬距	mm	476	476	480	495	
Fork	标准货叉 (长x宽x厚)	mm	40x122x1070	40x122x1070	45x125x1070	45x125x1070	
Service Weight	自重	kg	3400	3800	4280	4820	
Engine	Model	型号	JAC4DC1	ISUZU C240	YANMAR4TNE94L		
	Rated Output	额定功率	KW	45	35.4	42.1	
	Rated power speed	额定功率时转速	rpm	2500	2500	2300	

Engine Option: ISUZU/4JG2PE-01/44.9KW@2450/EC T2;YANMAR/4TNE98/42.1KW@2300/EU StageIII;MITSUBISHI/S4S-455/34.4@2250/Stage IIIA; Cummins/QSF2.8/34-55KW; KOHLER/KD11903TCR/42KW@2600/StageIV and Tier 4 Final.

