

项目/型号 Item/Model	ESB68	ESB75	ESB85	ESB100	ESB140	ESB155	ESB165	ESB175	ESB185	ESB190	ESB210
钎杆(活塞)直径/mm Diameter of drill rod (piston)	68	75	85	100	140	155	165	175	185	190	210
重量/kg Weight	250	380	510	785	1740	2413	2650	3788	3909	3950	6680
高度/mm Height	1330	1699	1767	1930	2414	2776	2919	3189	3315	3510	4000
宽度/mm Width	235	290	357	395	508	610	610	665	800	810	820
锤击频率/bpm Strike frequency	500-900	400-800	400-800	350-700	350-500	300-450	250-400	200-350	230-320	230-320	230-320
油压/MPa Oil pressure	11-14	12-15	13-16	15-17	16-18	16-18	16-18	19-21	19-21	19-21	19-21
排量/L/Min displacement	40-70	50-90	60-100	80-110	180-240	180-240	200-260	210-290	250-320	280-350	360-450
油管孔径/mm Tubing aperture	1/2	1/2	3/4	3/4	1	1.1/2	1.1/2	1.1/2	1.1/2	1.1/2	1.1/2
适用挖掘机/ton Suitable Excavator	4-7	6-9	7-14	11-16	18-26	28-35	30-45	40-55	50-60	50-60	60-90