



John Deere 125

## JOHN DEERE 125 SPECIFICATIONS

| General Specifications         |   |
|--------------------------------|---|
| <b>Model</b>                   | <b>John Deere 125</b>                     |
| <b>Length</b>                  | 1,750 mm (68.9 in)                        |
| <b>Width</b>                   | 1,310 mm (51.6 in)                        |
| <b>Height</b>                  | 1,080 mm (42.5 in)                        |
| <b>Wheel base</b>              | 1,240 mm (48.8 in)                        |
| <b>Weight</b>                  | 210 kg (463 lbs)                          |
| <b>Fuel tank capacity</b>      | 8.0 liters (2.1 US gal.; 1.8 Imp. gal)    |
| <b>Battery</b>                 | 12V, Type BCI Group U1                    |
| <b>Cabin type</b>              | Open operator station                     |
| Engine                         |   |
| <b>Engine model</b>            | <b>Briggs &amp; Stratton 44</b>           |
| <b>Engine type</b>             | Four-stroke, air-cooled, V-twin           |
| <b>Cylinders</b>               | 2   |
| <b>Fuel type</b>               | Gasoline                                  |
| <b>Displacement</b>            | 0.7 L, 724 cm <sup>3</sup> , (44.2 cu.in) |
| <b>Bore and stroke</b>         | 75.4 mm X 73.4 mm (2.97 in X 2.89 in)     |
| <b>Horsepower</b>              | 20.3 PS (14.9 kW; 20.0 HP)                |
| <b>Starter</b>                 | Electric                                  |
| <b>Oil type</b>                | SAE 10W-30; API: SG or SF                 |
| <b>Oil capacity:</b>           | 1.9 L (2 US. qt, 1.7 Imp. qt.)            |
| <b>Intake valve clearance</b>  | 0.102-0.152 mm (0.004-0.006 in)           |
| <b>Exhaust valve clearance</b> | 0.102-0.152 mm (0.004-0.006 in)           |
| <b>Spark plug gap</b>          | 0.76 mm (0.030 in)                        |



John Deere 125

### Transmission and chassis

|                           |   |
|---------------------------|---|
| <b>Chassis</b>            | 4x2 2WD   |
| <b>Steering type</b>      | Manual  |
| <b>Brakes</b>             | -   |
| <b>Transmission model</b> | <b>Tuff Torq T40</b>  |
| <b>Transmission type</b>  | Hydrostatic   |
| <b>Gears</b>              | Infinite forward and reverse                                    |
| <b>Speed</b>              | <b>Forward:</b> 8.9 kmh (5.5 mph) <b>Reverse:</b> 5.2 (3.2 mph) |

### Tires

|                    |                             |
|--------------------|-----------------------------|
| <b>Front tires</b> | <b>Lawn/turf:</b> 15x6.00-6 |
| <b>Rear tires</b>  | <b>Lawn/turf:</b> 20x8.0-8  |